



























DE		servogearless							beamer 2					
														
Aufhängung 2:1	Nennlast bis zu [kg]	2.000	1.150	1.150	1.050	1.500	1.800	3.000	1.600	3.000	4.000	5.000	5.000	9.800
	Geschwin- digkeit [m/s]	0,5 ... 1,6	0,5 ... 1,6	0,5 ... 1,0	0,63 ... 1,6	0,5 ... 2,0	0,5 ... 2,0	0,63 ... 3,5	0,63 ... 2,5	1,0 ... 5,0	1,0 ... 5,0	1,0 ... 5,0	1,0 ... 5,0	1,0 ... 6,0
Aufhängung 1:1	Nennlast bis zu [kg]	1.000	550	550	500	675	850	1.500	800	1.500	2.000	2.500	2.500	5.000
	Geschwin- digkeit [m/s]	1,0 ... 2,0	1,0 ... 2,0	1,0 ... 2,0	1,0 ... 2,0	0,5 ... 2,5	0,5 ... 3,0	1,0 ... 5,0	1,0 ... 5,0	1,0 ... 10,0	2,0 ... 10,0	2,0 ... 10,0	2,0 ... 10,0	2,0 ... 12,0
zulässige Achslast [kN]		24 ... 35	24 ... 35	35	24	26	45	100	55	140	200	300	300	520
Treibscheiben- durchmesser [mm]		100	120	(160), 180	120, 160	160, 210, 240, 320, 400, 480	210, 240, 270, 320, 400, 480, 520	320, 400, 480, 520, 600, 650, 686	340, 400	530, 610, 650, 686, (750)	530, 610, 650, 686, 750	650, (686), 750	650, (686), 750	(650), 800
EU Baumusterprüf- bescheinigung		EU-BD 1051 EU-BD 1056 EU-BD 1093 EU-BD 1055	EU-BD 1051 EU-BD 1056 EU-BD 1055	EU-BD 1056 EU-BD 1055	EU-BD 1093	EU-BD 1034 EU-BD 1056	EU-BD 1052 EU-BD 1053 EU-BD 1054	EU-BD 1077 EU-BD 1014/1	EU-BD 715	Inspecta 15656/1	EU-BD 908	EU-BD 1030	EU-BD 1030	EU-BD 1030
UL/CSA Zulassung		bald verfügbar	nein	nein	nein	nein	nein	ja	ja	ja	ja	ja	ja	nein
Motor		synchron, 14/16-polig	synchron, 14/16-polig	synchron, 16-polig	synchron, 14-polig	synchron, 16-polig	synchron, 20-polig	synchron, 20-polig	synchron, 22-polig	synchron, 22-polig	synchron, 22-polig	synchron, 22-polig	synchron, 22-polig	synchron, 20-polig
Abmessungen (ca.) [mm]		262 x 332 x 955	262 x 332 x 728	262 x 332 x 728	210 x 313 x 516	313 x 320 x 660	388 x 438 x 771	475 x 586 x 987	836 x 720 x 404	893 x 950 x 1059	970x1037x1232	1220x1110x1380	1220x1110x1380	1350x1355x2392
Gewicht (ca.) [kg]		100 ... 225	95 ... 171	150 ... 183	110 ... 130	121 ... 167	266 ... 368	570 ... 825	298 ... 420	1.126 ... 1.398	1.786 ... 1.935	2.610 ... 2.825	2.780 ... 3.000	7.920 ... 8.351
Hauptmerkmale		Speziell ent- wickelt für Polyropes und Riemen; kompaktes Design für reduzierten Schachtkopf	Speziell ent- wickelt für plastummantel- te Seile; kompaktes Design für reduzierten Schachtkopf	Für MRL- Ap- plikationen mit Standard-Stahl- seilen; kompaktes Design für reduzierten Schachtkopf	Für MRL- Ap- plikationen mit plastummantel- ten Seilen; kompaktes Design für reduzierten Schachtkopf	Speziell ent- wickelt für MRL- Applika- tionen; Seilablauf in alle Richtungen	Neuentwicklung speziell für MRL- Applika- tionen; Seilablauf in alle Richtungen	Neuentwicklung speziell für MRL- Applika- tionen; Seilablauf in alle Richtungen	Flaches Design für MRL und MR Lösungen; Seilablauf in alle Richtungen	Für intensiv ge- nutzte Anlagen und Bettenauf- züge; Seilablauf in alle Richtungen	Für Medium und Hochhaus Applikation; Seilablauf in alle Richtungen	Für Medium und Hochhaus Applikation; Seilablauf in alle Richtungen	Patentierter Maschinen für Hochhaus Modernisierun- gen; Seilablauf in alle Richtungen	Bestmögliche, getriebelose Schwerlast/ Hochhaus Auf- zugsmaschine; Seilablauf in alle Richtungen

WITTUR Electric Drives GmbH • Lift machines



WITTUR Electric
Drives GmbH



		<i>servogearless</i>							<i>beamer 2</i>					
EN														
		WSG-TB	WSG-TR	WSG-TS	WSG-RF	WSG-SF	WSG-MF	WSG-LF	WSG-08	WSG-21	WSG-25	WSG-29	WGG-29	WSG-52
Suspension 2:1	Rated load up to [kg]	2,000	1,150	1,150	1,050	1,500	1,800	3,000	1,600	3,000	4,000	5,000	5,000	9,800
	Rated speed [m/s]	0.5 ... 1.6	0.5 ... 1.6	0.5 ... 1.0	0.63 ... 1.6	0.5 ... 2.0	0.5 ... 2.0	0.63 ... 3.5	0.63 ... 2.5	1.0 ... 5.0	1.0 ... 5.0	1.0 ... 5.0	1.0 ... 5.0	1.0 ... 6.0
Suspension 1:1	Rated load up to [kg]	1,000	550	550	500	675	850	1,500	800	1,500	2,000	2,500	2,500	5,000
	Rated speed [m/s]	1.0 ... 2.0	1.0 ... 2.0	1.0 ... 2.0	1.0 ... 2.0	0.5 ... 2.5	0.5 ... 3.0	1.0 ... 5.0	1.0 ... 5.0	1.0 ... 10.0	2.0 ... 10.0	2.0 ... 10.0	2.0 ... 10.0	2.0 ... 12.0
Shaft load up to [kN]		24 ... 35	24 ... 35	35	24	26	45	100	55	140	200	300	300	520
Traction sheave diameter [mm]		100	120	(160), 180	120, 160	160, 210, 240, 320, 400, 480	210, 240, 270, 320, 400, 480, 520	320, 400, 480, 520, 600, 650, 686	340, 400	530, 610, 650, 686, (750)	530, 610, 650, 686, 750	650, (686), 750	650, (686), 750	(650), 800
EU type examination certification		EU-BD 1051 EU-BD 1056 EU-BD 1093 EU-BD 1055	EU-BD 1051 EU-BD 1056 EU-BD 1055	EU-BD 1056 EU-BD 1055	EU-BD 1093	EU-BD 1034 EU-BD 1056	EU-BD 1052 EU-BD 1053 EU-BD 1054	EU-BD 1077 EU-BD 1014/1	EU-BD 715	Inspecta 15656/1	EU-BD 908	EU-BD 1030	EU-BD 1030	EU-BD 1030
UL/CSA approved		available soon	no	no	no	no	no	yes	yes	yes	yes	yes	yes	no
Motor		synchronous, 14/16 poles	synchronous, 14/16 poles	synchronous, 16 poles	synchronous, 14 poles	synchronous, 16 poles	synchronous, 20 poles	synchronous, 20 poles	synchronous, 22 poles	synchronous, 22 poles	synchronous, 22 poles	synchronous, 22 poles	synchronous, 22 poles	synchronous, 20 poles
Dimension (approx.) [mm]		262 x 332 x 955	262 x 332 x 728	262 x 332 x 728	210 x 313 x 516	313 x 320 x 660	388 x 438 x 771	475 x 586 x 987	836 x 720 x 404	893 x 950 x 1059	970x1037x1232	1220x1110x1380	1220x1110x1380	1350x1355x2392
Weight (approx.) [kg]		100 ... 225	95 ... 171	150 ... 183	110 ... 130	121 ... 167	266 ... 368	570 ... 825	298 ... 420	1,120 ... 1,300	1,786 ... 1,935	2,610 ... 2,825	2,780 ... 3,000	7,920 ... 8,351
Key Characteristics		Especially developed for Polyropes/belts; compact design for reduced headroom	Especially developed for ropes with plastic sheathing; compact design for reduced headroom	Developed for MRL- solutions for standard steel ropes; compact design for reduced headroom	Developed for MRL- solutions for ropes with plastic sheathing; compact design for reduced headroom	Especially developed for machine-room-less (MRL) solutions; rope tension in all directions	A new innovation developed especially for machine-room-less (MRL) solutions; rope tension in all directions	A new innovation developed especially for machine-room-less (MRL) solutions; rope tension in all directions	Flat design for MRL and MR solutions; rope tension in all directions	Intensive use lifts and health-care lifts; rope tension in all directions	Mid- and High-Rise applications; rope tension in all directions	Mid- and High-Rise applications; rope tension in all directions	Patented split housing gearless for High-Rise mod; rope tension in all directions	The top of the range, heavy-duty, high-rise gearless traction machine; rope tension in all directions