

		W LINE PULLEYS ON TOP (320 ≤ Q ≤ 1000)																				
Rated Load	kg	320	400	450		630			800				1000									
Suspension		2:1	2:1	2:1		2:1			2:1				2:1									
Rated Speed	m/s	1	1	1	1,6	1	1,6	2	1	1,6	2	2,5	1	1,6	2	2,5	3					
Max. Travel Height	m	30	30	30	60	30	60	90	30	60	90	120	30	60	90	120	150					
Max load on safety	Kg	1030 - 1135	1165 - 1285	1235 - 1370		1480 - 1650			1765 - 1950				1960 - 2170	2120 - 2380			2380 - 2650					
Shaft Dimensions																						
Min. Shaft Width SW	mm	CIW + 515	CIW + 515	CIW + 515	CIW + 520	CIW + 515	CIW + 520	CIW + 535	CIW + 520	CIW + 535			CIW + 700	CIW + 520	CIW + 535		CIW + 700					
Max. Shaft Width SW	mm	CIW + 1140	CIW + 1140	CIW + 1140	CIW + 1145	CIW + 1140	CIW + 1145	---	CIW + 1145	CIW + 1160			CIW + 1400	CIW + 1145	CIW + 1160		CIW + 1400					
Shaft Depth SD	mm	CID + 80 + ESD + X (Door package)	CID + 80 + ESD + X (Door package)	CID + 80 + ESD + X (Door package)		CID + 80 + ESD + X (Door package)			CID + 80 + ESD + X (Door package)				CID + 80 + ESD + X (Door package)									
Standard Pit SP	mm	1000	1000	1000	1100	1000	1100	1200	1000		1100		1200		1550	1000		1100		1200	1550	1820
Standard Headroom (700 mm balustrade)	mm	CIH + 1400	CIH + 1400	CIH + 1400	CIH + 1560	CIH + 1400	CIH + 1560	CIH + 1660	CIH + 1400	CIH + 1500	CIH + 1560	CIH + 1660	CIH + 1660	CIH + 1760	CIH + 2935	CIH + 1400	CIH + 1500	CIH + 1560	CIH + 1660	CIH + 1760	CIH + 2935	CIH + 3025
Standard Headroom (1100 mm balustrade)	mm	CIH + 1670	CIH + 1670	CIH + 1670	CIH + 1830	CIH + 1670	CIH + 1830	CIH + 1930	CIH + 1670		CIH + 1830		CIH + 1930		CIH + 2935	CIH + 1670		CIH + 1830		CIH + 1930	CIH + 2935	CIH + 3025
Doors																						
Clear opening	mm	600 - 1600		600 - 1600		600 - 1600			600 - 1600				600 - 1600									
Clear height	mm	2000 - 2600		2000 - 2600		2000 - 2600			2000 - 2600				2000 - 2600									
Cars																						
Max. CIW	mm	700 - 1100		700 - 1400		900 - 1500			900 - 1600				1000 - 2100									
Max. CID	mm	800 - 1200		800 - 1400		850 - 1450			1100 - 1600				1200 - 2400									
CIH	mm	2000 - 3000		2000 - 3000		2000 - 3000			2000 - 3000				2000 - 3000									
Controller																						
Model		E-Pack Plus E-Pack Evo (only available for standard pit and headroom)																				
COP		E-Pack Plus - Ocean Series / E-Pack Evo - Sunset Series Surface mounted Half height / Full height Dot matrix / TFT																				
LOP		E-Pack Plus - Ocean Series / E-Pack Evo - Sunset Series Surface mounted Without display / Dot matrix / TFT																				