



Wittur CORE

LANDING DOOR

A NEW GLOBAL DOOR PLATFORM FOR LOW RISE



*safety in motion*TM

Wittur CORE

LANDING DOOR

A NEW GLOBAL DOOR PLATFORM FOR LOW RISE

PRODUCT PARAMETERS & RANGE

Door Type	C2
Sill Depth	40 mm
Side Frame Dim.	50 mm × 40 mm
Top Frame Dim.	50 mm
Options	Grout Guard
Sill Load	400 Kg
Lift Speed	up to 2.5 m/s

CO _{mm}	700	800	900	1000
CH _{mm}	2000-2100			

CO = Clear Opening
CH = Clear Height

SAFETY

- ▶ Anti-dropping hooks on the door panel for sill (patented) and back of truck

PERFORMANCE

- ▶ Bearings mounted on all truck, synchronisation and counter rollers
- ▶ Arc-shaped, double rail guiding profile
- ▶ High-performance PA landing lock rollers

RELIABILITY

- ▶ Trapezoidal rail support increases radial force resistance
- ▶ Black electrophoresis treatment for all key parts in the landing door hanger

EASY INSTALLATION

- ▶ 3D adjustable interface to panels
- ▶ Light weight and reduced number of parts for fast installation
- ▶ Integrated reclosing device
- ▶ Single adjustment for lock rollers
- ▶ Asymmetric bottom shoes
- ▶ Hook for mechanism

EASY MAINTENANCE

- ▶ Most components are assembled with screws and replaceable including brackets on side frames
- ▶ All components are easily accessible

REGULATION CODE

- ▶ GB7588:2003+XG1 :2016
- ▶ EN81-20/50
- ▶ CCC for electrical components
- ▶ EN81-58 E120
- ▶ Fulfillment of CTE certificate
- ▶ Fulfillment of CE certificate